

ORLIK[®]

COMPRESSORS **original**

Piston compressors range 17 - 28 - 40 - 51



PKS 17/150



PKS 28/185



SKS 28/250



EKA 28



EKA 40



PKS 40/300

Piston compressors ORLIK original are used in heavy duty industry

Piston compressors range 17 - 28 - 40 - 51

Main advantages of compressors ORLIK original:

- First-class quality warranted with the long tradition of the production of piston compressors
- Guarantee 6 years on the tank and 3 years on the compressor
- Nearly maintenance-free
- Easy compatibility of spare parts

■ Range 17

Type	Suction capacity (m ³ /h)	Capacity related to suction (m ³ /h)	Max. overpressure (bar)	Automatic cycle range (bar)	Electromotor Output (kW)	Electromotor Voltage (V)	Average noise level (dB)	Connection dimension	Weight (kg)	Pressure tank volume (l)	Dimensions L x W x H (mm)
EKA 17	26,9	17	10	10	3	3 x 400	80	M22x1,5	48	-	560 x 370 x 540
PKS 17/150	26,9	17	10	10	3	3 x 400	80	G1/4"	96	150	1296 x 525 x 1063
SKS 17/250	26,9	17	10	10	3	3 x 400	80	G1/2"	123	250	610 x 600 x 1607

■ Range 28

Type	Suction capacity (m ³ /h)	Capacity related to suction (m ³ /h)	Max. overpressure (bar)	Automatic cycle range (bar)	Electromotor Output (kW)	Electromotor Voltage (V)	Average noise level (dB)	Connection dimension	Weight (kg)	Pressure tank volume (l)	Dimensions L x W x H (mm)
EKA 28	44	28	10	-	4	3 x 400	84	M22x1,5	70	-	578 x 648 x 495
PKS 28/185	44	28	10	6,5 - 9	4	3 x 400	84	G1/2"	145	185	1111 x 648 x 1115
PKS 28/300	44	28	10	6,5 - 9	4	3 x 400	84	G1/2"	176	300	1710 x 648 x 1115
SKS 28/250	44	28	10	6,5 - 9	4	3 x 400	84	G1/2"	152	250	655 x 648 x 1553

■ Range 40 - 51

Type	Suction capacity (m ³ /h)	Capacity related to suction (m ³ /h)	Max. overpressure (bar)	Automatic cycle range (bar)	Electromotor Output (kW)	Electromotor Voltage (V)	Average noise level (dB)	Connection dimension	Weight (kg)	Pressure tank volume (l)	Dimensions L x W x H (mm)
2 DSK 120	67,6	40 - 51*	10	-	-	-	85	G3/4"	62	-	430 x 455 x 565
EKA 40	51,5	40	10	-	5,5	3 x 400	85	G3/4"	139	-	1003 x 530 x 755
EKA 40/12	48,3	38	12	-	5,5	3 x 400	85	G3/4"	139	-	1003 x 530 x 755
PKS 40/300	51,5	40	10	6,5 - 9	5,5	3 x 400	85	G3/4"	239	300	1785 x 620 x 1310
PKS 40/300/12	48,3	38	12	9 - 12	5,5	3 x 400	85	G3/4"	257	300	1785 x 620 x 1310
EKA 51	67,6	51	10	-	7,5	3 x 400	85	G3/4"	164	-	1003 x 530 x 755
PKS 51/300	67,6	51	10	6,5 - 9	7,5	3 x 400	85	G3/4"	264	300	1785 x 620 x 1310

- Compressors without a pressure tank are designed for an environment with an ambient temperature of -5°C do +40°C.
- Compressors with a pressure tank are designed for an environment with an ambient temperature of +5°C do +40°C.

*With the electromotor 7,5 kW

COMPRESSORS WITH A PRESSURE TANK OPERATE IN THE RANGE OF THE AUTOMATIC CYCLE ACCORDING TO THE TABLE.

Your distributor and professional adviser: